

Bosch LB20-PC30-5L Quick Install Speaker 5 inch Cabinet 70/100V/White/IP54 (Pair)

Frequency response (-3 dB):	85 Hz - 20 kHz ¹
Frequency response (-10 dB):	60 Hz - 20 kHz ¹
Sensitivity:	90 dB ²
Max SPL (calculated):	109 dB (115 dB Peak)
Coverage angle:	Horizontal 90°, Vertical 90°
Power handling:	75 W (300 W Peak) Continuous Pink Noise (100 hours)
Low Z:	Yes
Nominal impedance:	8 Ω
Minimum impedance:	6 Ω
Recommended High-Pass:	60 Hz (24 dB/octave)
Input transformer (70 V/100 V):	30 W
Transformer taps:	70 V: 3.7 W, 7.5 W, 15 W, 30 W, 8 Ω 100 V: 7.5 W, 15 W, 30 W, 8 Ω
LF transducer:	5.25 inch (133 mm)
HF transducer:	0.75 inch (20 mm)
Connectors:	Captive screws on wall bracket. Removable locking 4-pin connector (Euroblock) - (2) for connection to additional speakers in a distributed line. Max. wire size 12AWG (2.5 mm)
Environmental:	IP54 (per IEC-60529)
Color:	White (RAL 9003)
Dimensions (H x W x D):	255 mm x 180 mm x 154 mm (10.0 in x 7.1 in x 6.0 in) ³
Net weight:	3.2 kg (7.0 lb) ³
Shipping weight (pair):	7.9 kg (17.5 lb)
Included hardware:	Mounting bracket and 5-mm Allen wrench
Packaged quantity:	2