

# Microphone

---

Form Factor	Desktop / Gooseneck
-------------	---------------------

---

Capsule	Condenser
---------	-----------

---

Polar Pattern	Cardioid, Unidirectional
---------------	--------------------------

---

## Performance

---

Frequency Range	100 Hz to 16 kHz
-----------------	------------------

---

Maximum SPL	110 dB SPL
-------------	------------

---

Impedance	200 Ohms
-----------	----------

---

Sensitivity	2 mV/Pa
-------------	---------

---

Signal-to-Noise Ratio	66 dB A-Weighted (at 1 Pa/94 dB SPL)
-----------------------	--------------------------------------

---

Equivalent Noise Level	28 dB SPL A-Weighted
------------------------	----------------------

---

THD	< 0.6% ⓘ
-----	----------

---

## Connectivity

---

Output Connectors	<b>1 x</b> Euroblock 5-Pin
-------------------	----------------------------

---

Cable Length	6.6' / 2 m
--------------	------------

---

## Power

---

Operating Voltage 12 to 48 V (Phantom Power)

---

Operating Current Consumption 8 mA

---

## Physical

---

Color Black

---

Construction Material Metal, Rubber

---

Operating Temperature -13 to 131°F / -25 to 55°C

---

Operating Humidity 0 to 95%

---

Storage Temperature -40 to 158°F / -40 to 70°C

---

Dimensions H: 1.57 x W: 3.97 x L: 9.25" / H: 40.00 x W: 100.00 x L: 235.00 mm (Base)  
L: 15.35" / L: 390.00 mm (Gooseneck, Microphone)

---

Weight 2.2 lb / 1 kg

---