

# Microphone

---

Form Factor	Desktop / Gooseneck
Capsule	Condenser
Polar Pattern	Cardioid, Unidirectional
High-Pass Filter	315 Hz, 6 dB/Octave ⓘ
Gain Adjustment	-15 to +6 dB ⓘ
Indicators	<b>6 x</b> Chime <b>2 x</b> Single LED

---

# Performance

---

Frequency Range	100 Hz to 16 kHz
Maximum SPL	110 dB SPL
Impedance	200 Ohms
Sensitivity	85 dB SPL ⓘ
Output Level	700 mV
Equivalent Noise Level	25 dB SPL A-Weighted
THD	< 0.6% ⓘ

---

## Connectivity

---

Output Connectors **2 x RJ45**

---

Cable Length 16.4' / 5 m

---

## Power

---

Operating Voltage 24 V

---

Operating Current Consumption 30 mA

---

## Physical

---

Color Black

---

Construction Material Metal, Rubber

---

Operating Temperature -13 to 131°F / -25 to 55°C

---

Operating Humidity 0 to 95%

---

Storage Temperature -40 to 158°F / -40 to 70°C

---

Dimensions H: 1.57 x W: 3.97 x L: 9.25" / H: 40.00 x W: 100.00 x L: 235.00 mm (Base)  
L: 15.35" / L: 390.00 mm (Gooseneck, Microphone)

---

Weight 2.2 lb / 1 kg

---

