

Adder AVX1016-USA 16 Port High density fully featured USB/Video KVM Switcher

Hardware compatibility

Supports PC, RS/6000, Alpha, SGI, Sun and Apple with USB / PS/2 / Sun style keyboard and mouse and VGA video interfaces

Software compatibility

Operates with all known software and operating systems including Windows (all), DOS, Linux, Unix, BSD, all Sun OS, all Mac OS, NetWare etc.

Computer connections at switch

RJ45

Computer connections at computer

Video: HDD15, Keyboard/Mouse: choice of USB, PS/2 and Sun MiniDin8 Audio (optional): 3.5mm stereo jack

Local KVM console connection

Video: HDD15, Keyboard/Mouse: USB type A, Audio: 3.5mm stereo jack

Physical design

1U high 198mm / 7.92"(w), 44mm / 1.76"(h), 120mm / 4.8"(d), 750g / 1.65 lbs. 1 per 1U or 2 per 1U rack mount kits available

Power connection

2.5mm DC jack, power adapter included

Other connectors

Remote KVM console: RJ45, Options (flash upgrade, sync with other CATx1000 and RS232 triggered power switches): DB9 female

Power

100-240VAC 50/60Hz input to power adapter, 5VDC 2A output from power adapter

Operating temperature

0 - 40 deg C (32 to 104 deg F)

Approvals

CE, FCC

Order codes

AVX1008-XX: 8 port version AVX1016-XX: 16 port version

XX= Mains Lead Country Code: UK = United Kingdom US = United States EURO = Europe AUS = Australia

Additional accessories

RMK4S: Single rack brackets RMK4D: Dual rack brackets CAB-9M/9F-2M Serial option cable