

Electro-Voice EKX12 1400 Watt Passive 12 inch 2-Way Loudspeaker/55Hz-20KHz

Axial Sensitivity (SPL, 1 W @ 1 m)	95 dB
Connector Type	Dual NL4
Coverage (Nominal -6 dB) H	90 °
Crossover Frequency	1.6 k Hz
Depth	356 mm
Enclosure Material	15 mm, plywood with EVCoat
Family	EKX
Frequency Response (-10 dB)	55 Hz - 20 k Hz
Frequency Response (-3 dB)	82 Hz - 18 k Hz
Grill	18 AWG steel with powdercoat
Height	607 mm
HF Transducer	DH-1M 1-inch titanium compression driver
LF Transducer	EVS-12M 300 mm (12 in)
Max. SPL/1m (calc)	131 dB
Maximum SPL	131 dB
Minimum Impedance	7.5 Ω
Nominal Impedance	8 Ω
Passive Power Handling	1400 W peak
Power Handling (Continuous / Peak)	350 W/1400 W
Power Rating	1400 W
Powered or Passive	Passive
Recommended High-Pass Frequency	55 Hz
Shipping Weight	21.4 kg
Speaker Type	Full-Range, two-way
Suspension	(8) M10 threaded mounting points
Weight Net	17.4 kg
Width	375 mm
Woofers Size	12 mm