

## Electro-Voice EKX15 1600 Watt Passive 15 inch 2-Way Loudspeaker/50Hz-20KHz

Axial Sensitivity (SPL, 1 W @ 1 m)	96 dB
Connector Type	Dual NL4
Coverage (Nominal -6 dB) H	90 °
Coverage (Nominal -6 dB) V	60 °
Crossover Frequency	1.6 k Hz
Depth	429 mm
Enclosure Material	15 mm, plywood with EVCoat
Family	EKX
Frequency Response (-10 dB)	50 Hz - 20 k Hz
Frequency Response (-3 dB)	75 Hz - 18 k Hz
Grill	18 AWG steel with powdercoat
Height	685 mm
HF Transducer	DH-1M 1-inch titanium compression driver
LF Transducer	EVS-15M 381 mm (15 in)
Max. SPL/1m (calc)	132 dB
Maximum SPL	132 dB
Minimum Impedance	7.2 $\Omega$
Nominal Impedance	8 $\Omega$
Passive Power Handling	1600 W peak
Power Handling (Continuous / Peak)	400 W/1600 W
Power Rating	1600 W
Powered or Passive	Passive
Recommended High-Pass Frequency	50 Hz
Shipping Weight	28.2 kg
Speaker Type	Full-Range, two way
Suspension	(8) M10 threaded mounting points
Weight Net	23.2 kg
Width	432 mm
Woofer Size	15 mm