

## Electro-Voice EKX15S 1600 Watt Passive 15 inch Subwoofer/40Hz-300Hz

|                                    |                              |
|------------------------------------|------------------------------|
| Axial Sensitivity (SPL, 1 W @ 1 m) | 95 dB                        |
| Connector Type                     | Dual NL4                     |
| Depth                              | 551 mm                       |
| Enclosure Material                 | 15 mm, plywood with EVCoat   |
| Family                             | EKX                          |
| Frequency Response (-10 dB)        | 40 Hz - 300 Hz               |
| Frequency Response (-3 dB)         | 60 Hz - 100 Hz               |
| Grill                              | 18 AWG steel with powdercoat |
| Height                             | 455 mm                       |
| LF Transducer                      | EVS-15C 381 mm (15 in)       |
| Max. SPL/1m (calc)                 | 133 dB                       |
| Maximum SPL                        | 133 dB                       |
| Minimum Impedance                  | 7.5 $\Omega$                 |
| Nominal Impedance                  | 8 $\Omega$                   |
| Passive Power Handling             | 1600 W peak                  |
| Power Handling (Continuous / Peak) | 400 W/1600 W                 |
| Power Rating                       | 1600 W                       |
| Powered or Passive                 | Passive                      |
| Recommended High-Pass Frequency    | 35 Hz                        |
| Shipping Weight                    | 31.3 kg                      |
| Speaker Type                       | Subwoofer                    |
| Weight Net                         | 24.9 kg                      |
| Width                              | 530 mm                       |
| Woofer Size                        | 15 mm                        |