

Electro-Voice ELX112 Passive 12 inch 2-Way Full-Range Loudspeaker/55Hz-20KHz

Available Color	Black
Axial Sensitivity (SPL, 1 W @ 1 m)	94 dB
Case Material	9-ply, 15mm Plywood, Internally Braced, with Textured Paint
Connector Type	Parallel Neutrik® NL4
Coverage (Nominal -6 dB) H	90 °
Coverage (Nominal -6 dB) V	50 °
Crossover Frequency	21000 Hz
Depth	340 mm
Enclosure Material	9-ply plywood
Family	ELX
Frequency Response (-10 dB)	55 - 20000 Hz
Frequency Response (-3 dB)	82 - 18000 Hz
Grill	18GA Steel with Black Powdercoat
Height	607 mm
HF Transducer	DH-1K, 39mm (1.5") Titanium Diaphragm Compression Driver
Internal Crossover	Yes
LF Transducer	(1) EVS-12K, 305mm (12") Woofer
Max. SPL/1m (calc)	132 dB
Minimum Impedance	7.0 Ω
Nominal Impedance (Passive)	8 Ω
Powered or Passive	Passive
Recommended High-Pass Frequency	45 Hz
Speaker Type	Full-Range, two-way, wedges
System Power Handling (Continuous/Program/Peak)	250//1000 Watts
Weight Net	16 kg
Width	362 mm
Woofer Size	12 mm