

**Electro-Voice ELX115 Passive 15 inch 2-Way Full-Range Loudspeaker/50Hz-20KHz**

Available Color	Black
Axial Sensitivity (SPL, 1 W @ 1 m)	95 dB
Case Material	9-ply, 15mm Plywood, Internally Braced, with Textured Paint
Connector Type	Parallel Neutrik® NL4
Coverage (Nominal -6 dB) H	90 °
Coverage (Nominal -6 dB) V	50 °
Crossover Frequency	17000 Hz
Depth	382 mm
Enclosure Material	9-ply plywood
Family	ELX
Frequency Response (-10 dB)	50 - 20000 Hz
Frequency Response (-3 dB)	75 - 18000 Hz
Grill	18GA Steel with Black Powdercoat
Height	708 mm
HF Transducer	DH-1K, 39mm (1.5";) Titanium Diaphragm Compression Driver
Internal Crossover	Yes
LF Transducer	(1) EVS-15K, 381mm (15";) Woofer
Max. SPL/1m (calc)	134 dB
Minimum Impedance	7.4 Ω
Nominal Impedance (Passive)	8 Ω
Powered or Passive	Passive
Recommended High-Pass Frequency	40 Hz
Speaker Type	Full-Range, mid-high, two-way
System Power Handling (Continuous/Program/Peak)	400//1600 Watts
Weight Net	21.9 kg
Width	432 mm
Woofer Size	15 mm