

Electro-Voice ELX215 Dual 15 inch 2-Way Full-Range Loudspeaker/38Hz-20KHz

Available Color	Black
Axial Sensitivity (SPL, 1 W @ 1 m)	96 dB
Case Material	9-ply, 15mm Plywood, Internally Braced, with Textured Paint
Connector Type	Parallel Neutrik® NL4
Coverage (Nominal -6 dB)	Omnidirectional
Coverage (Nominal -6 dB) H	90 °
Coverage (Nominal -6 dB) V	50 °
Crossover Frequency	1.7 k Hz
Depth	501 mm
Enclosure Material	9-ply plywood
Family	ELX
Frequency Response (-10 dB)	38 - 20000 Hz
Frequency Response (-3 dB)	62 - 18000 Hz
Grill	18GA Steel with Black Powdercoat
Height	1154 mm
HF Transducer	DH-1K, 39mm (1.5") Titanium Diaphragm Compression Driver
Internal Crossover	Yes
LF Transducer	(2) EVS-15K, 381mm (15") Woofers
Max. SPL/1m (calc)	137 dB
Minimum Impedance	3.7 Ω
Nominal Impedance (Passive)	4 Ω
Powered or Passive	Passive
Recommended High-Pass Frequency	35 Hz
Shipping Weight	52.0 kg
Speaker Type	Full-Range, mid-high, two-way
System Power Handling (Continuous/Program/Peak)	600//2400 Watts
Weight Net	40.7 kg
Width	432 mm
Woofers Size	15 mm