

**Electro-Voice TX1122 2000 Watt 12 inch 2-Way Full-Range Loudspeaker/60Hz-20KHz**

Available Color	Black
Coverage (Nominal -6 dB) H	90 °
Coverage (Nominal -6 dB) V	50 °
Crossover Frequency	1600 Hz
Depth	573 mm
Enclosure Material	Ply Wood and MDF with EVCOAT
Family	Tour X
Flying	Yes
Frequency Response (-10 dB)	45 - 20000 Hz
Frequency Response (-3 dB)	70 - 20000 Hz
Height	440 mm
HF Transducer	1.25-inch DH3/2010A
Input Connections	Parallel Neutrik® NL4
Internal Crossover	Yes
LF Transducer	12-inch SMX2121
Max. SPL/1m (calc)	132 dB
Minimum Impedance	6.4 Ω
Nominal Impedance (Passive)	8 Ω
Power Rating	2000 W
Powered or Passive	Passive
Recommended High-Pass Frequency	45 Hz
Rotatable Horn	No
Sensitivity 1 W/1 m	97 dB
Speaker Type	Full-Range
Suspension	(6) 3/8-inch threaded inserts
System Power Handling (Continuous/Program/Peak)	500//2000 Watts
Weight Net	19.8 kg
Width	364 mm
Woofer Size	12 mm