

Electro-Voice TX2152 4000 Watt Dual 15 inch 2-Way Full-Range Loudspeaker/55Hz-13KHz

Available Color	Black
Coverage (Nominal -6 dB) H	60 °
Coverage (Nominal -6 dB) V	40 °
Crossover Frequency	1750 Hz
Depth	471 mm
Enclosure Material	Plywood and MDF with EVCOAT
Family	Tour X
Flying	Yes
Frequency Response (-10 dB)	50 - 18000 Hz
Frequency Response (-3 dB)	55 - 13000 Hz
Height	1154 mm
HF Transducer	2-inch ND2
Input Connections	Parallel Neutrik® NL4
Internal Crossover	Yes
LF Transducer	Two 15-inch SMX2151
Max. SPL/1m (calc)	139 dB
Minimum Impedance	3.1 Ω
Nominal Impedance (Passive)	4 Ω
Power Rating	4000 W
Powered or Passive	Passive
Recommended High-Pass Frequency	40 Hz
Rotatable Horn	Yes
Sensitivity 1 W/1 m	103 dB
Speaker Type	Full-Range
Suspension	(6) 3/8-inch threaded inserts
System Power Handling (Continuous/Program/Peak)	1000//4000 Watts
Weight Net	42.8 kg
Width	508 mm
Woofer Size	15 mm