

Electro-Voice ZLX12 1000 Watt Passive 12 inch 2-Way Loudspeaker/55Hz-18KHz/Black

Axial Sensitivity (SPL, 1 W @ 1 m)	95 dB
Connector Type	Dual NL4
Coverage (Nominal -6 dB) H	90 °
Coverage (Nominal -6 dB) V	60 °
Crossover Frequency	2100 Hz
Depth	356 mm
Enclosure Material	Polypropylene Composite
Family	ZLX
Frequency Range	55 Hz - 20 kHz
Frequency Response	82 Hz - 18 kHz
Grill	18 Gauge Steel with Black Powder Coat
Height	610 mm
HF Transducer	DH-1K
LF Transducer	EVS-12K, 300 mm (12 in) Woofer
Max. SPL/1m (calc)	125 dB
Maximum SPL	125 dB
Minimum Impedance	7 Ω
Nominal Impedance	8 Ω
Passive Power Handling	1000 W peak
Power Handling (Continuous / Peak)	250 / 1000 W
Power Rating	1000 W
Powered or Passive	Passive
Recommended High-Pass Frequency	40 Hz
Shipping Weight	18 kg
Speaker Type	Full-Range
Weight Net	14.9 kg
Width	356 mm
Woofer Size	12 mm