

Electro-Voice ZLX15 1000 Watt Passive 15 inch 2-Way Loudspeaker/44Hz-20KHz/Black

Axial Sensitivity (SPL, 1 W @ 1 m)	96 dB
Connector Type	Dual NL4
Coverage (Nominal -6 dB) H	90 °
Coverage (Nominal -6 dB) V	60 °
Crossover Frequency	1700 Hz
Depth	383 mm
Enclosure Material	Polypropylene Composite
Family	ZLX
Frequency Range	44 Hz - 20 kHz
Frequency Response	56 Hz - 18 kHz
Grill	18 Gauge Steel with Black Powder Coat
Height	685 mm
HF Transducer	DH-1K
LF Transducer	EVS-15L, 380 mm (15 in) Woofer
Max. SPL/1m (calc)	126 dB
Maximum SPL	126 dB
Maximum SPL (1% THD)	0 dB
Minimum Impedance	7 Ω
Nominal Impedance	8 Ω
Passive Power Handling	1000 W peak
Power Handling (Continuous / Peak)	250 / 1000 W
Power Rating	1000 W
Powered or Passive	Passive
Recommended High-Pass Frequency	40 Hz
Shipping Weight	22 kg
Speaker Type	Full-Range, two-way
Weight Net	16.6 kg
Width	423 mm
Woofer Size	15 mm