

BZBGEAR BG-UHD-KVM41-KIT 4-Port 4K UHD KVM and Conference Room Switcher with HDMI and USB 3.0 Kit with 4 Table Grommets

Video Input	
Input	(4) SOURCE 1~4
Input Connector	(4) Female type-A HDMI
HDMI Input Resolution	Up to 4Kx2K @ 60Hz 4:4:4, HDR10, Dolby Vision
HDMI Standard	2.0
HDCP Version	2.2
Video Output	
Output	(1) DISPLAY
Output Connector	(1) Female type-A HDMI
HDMI Output Resolution	Up to 4Kx2K @ 60Hz 4:4:4, HDR10, Dolby Vision
HDMI Standard	2.0
HDCP Version	2.2
Audio	
Output	(1) AUDIO OUT
Output Connector	(1) 3.5mm mini stereo audio jack
Audio Format	PCM 2CH
Frequency Response	20Hz to 20KHz, ± 1 dB
Max Output Level	2.0Vrms \pm 0.5dB. 2V = 16dB headroom above -10dBV (316 mV) nominal consumer line level signal.
THD+N	< 0.05%, 20Hz - 20KHz bandwidth, 1KHz sine at 0dBFS level (or max level).
SNR	> 80dB, 20Hz - 20KHz bandwidth.
Crosstalk Isolation	< -80 dB, 10 kHz sine at 0dBFS level (or max level before clipping).
L-R Level Deviation	< 0.05 dB, 1 kHz sine at 0dBFS level (or max level before clipping).
Output Load Capability	1Kohm and higher (supports 10x paralleled 10k ohm loads).
Noise Level	-80dB
Control	
Control	(1) FW, (4) PC 1~4, (3) DEVICES 1~3, (4) GR 1~4, (1) RS232
Control Connector	(1) Micro-USB, (4) Type-B USB, (3) Type-A USB, (5) 3-pin Terminal Blocks
General	
Bandwidth	18Gbps
Operation Temperature	14°F ~ +131°F / -10°C ~ +55°C
Storage Temperature	-25°F ~ +158°F / -25°C ~ +70°C
Relative Humidity	10%-90%
Type-A USB Power Supply	1A
System Power Supply	Input: 100V~240V AC; Output: 12V DC 2A
System Power Consumption	14W(Max)
Dimension (W*H*D)	7.9" x 1.6" x 3.9" [200mm x 40mm x 100mm]
Net Weight	1.5lbs [685g]

BG-SC-GRHU Table Grommet

Video Input	
Input	(1) HDMI

Input Connector	(1) Female type-A HDMI
Video Output	
Output	(1) HDMI
Output Connector	(1) Female type-A HDMI
Control	
Control Connector	(1) Type-B USB, (1) Type-A USB, (1) 3-pin Terminal Block
General	
Resolution Range	Up to 4Kx2K @ 60Hz 4:4:4, HDR10, Dolby Vision
Operation Temperature	14-25°F ~ +131-25°F / -10°C ~ +55°C
Storage Temperature	-25-25°F ~ +158-25°F / -25°C ~ +70°C
Relative Humidity	10%-90%
Dimension (W*H*D)	3.0" x 1.2" x 3.0" [76mm x 29.6mm x 76mm]
Net Weight (g)	0.23lbs [105g]