

BZBGEAR BG-PS21-4K 2-Port 4K UHD KVM and Presentation Switcher with HDMI, USB-C and USB 3.0

Video	
Video Input	(1) HDMI, (1) USB-C
Video Input Connector	(1) Type-A female HDMI, (1) Type-C USB
HDMI Input Resolution	Up to 4Kx2K @ 60Hz 4:4:4 8bit
USB-C Input Resolution	Up to 4Kx2K @ 30Hz 4:4:4
Video Output	(1) HDMI
Video Output Connector	(1) Type-A female HDMI
HDMI Output Resolution	Up to 4Kx2K @ 60Hz 4:4:4 8bit
HDMI Version	2.0
HDCP Version	2.2
USB Version	3.0
HDR 10	Supported
CEC	Supported
HPD	Supported
Audio	
Audio Output	(1) AUDIO OUT (Stereo balanced L/R)
Audio Output Connector	(1) 5-pin terminal block
HDMI Audio Format	LPCM 7.1 audio, Dolby Atmos®, Dolby® TrueHD, Dolby Digital® Plus, DTS: X™, and DTS-HD® Master Audio™ pass-through
Stereo balanced L/R audio Format	PCM
Max Output Level	2.0Vrms ± 0.5dB. 2V = 16dB headroom above -10dBV (316mV) nominal consumer line level signal
THD+N	<0.05% (-80dB), 20Hz ~ 20KHz bandwidth, 1KHz sine at 0dBFS level (or max level)
SNR	>80dB, 20Hz ~ 20KHz bandwidth
Crosstalk Isolation	>70dB, 10KHz sine at 0dBFS level (or max level before clipping)

L-R Level Deviation	< 0.3dB, 1KHz sine at 0dBFS level (or max level before clipping)
Frequency Response Deviation	<±0.5dB 20Hz ~ 20KHz
Output Load Capability	1KΩ and higher (supports 10x paralleled 10KΩ loads)
Stereo Channel Separation	>70dB @ 1KHz
Control Part	
Control	(1) EDID, (1) FW, (1) RS232, (1) HOST, (2) DEVICE
Control Connector	(1) 4-pin DIP switch, (1) Micro-USB, (1) 3-pin terminal block, (1) Type-B USB 3.0, (2) Type-A USB 3.0
General	
HDMI 2.0 Cable Length	4K @ 60Hz 4:4:4 ≤ 5m, 4K @ 60Hz 4:2:0 ≤ 10m, 1080P ≤ 15m
Bandwidth	18Gbps
Operation Temperature	14°F ~ 131°F / -10°C ~ +55°C
Storage Temperature	-13°F ~158°F / -25°C ~ +70°C
Relative Humidity	10% ~ 90%
External Power Supply	Input: AC 100~240V, 50/60Hz, Output: 24V DC 2.71A
Power Consumption	54W (Max)
Dimension (W*H*D)	6.6" x 1.0" x 3.7" [168.0mm x 24.5mm x 95.0mm]
Net Weight	0.54lbs [245g]