

Supported Operating Systems	macOS 10.13, 10.14 or Later Windows 7, 8.1, 10 (All 64-Bit) Linux
Inputs/Outputs	4 x HDMI 2.0b
Computer Interface	PCI Express 8 Lane Generation 3 (Compatible with 8 and 16 Lane PCI Express Slots)
Audio Channels	8 x Embedded (HD and SD)
Video Support	DCI 4K: 4K: 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 UHD 4K: 2160p: 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 HD: 1080p: 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 1080PsF: 23.98, 24, 25, 29.97, 30 1080i: 50, 59.94, 60 720p: 50, 59.94, 60 DVI: 2560 x 1600p: 50, 60 2560 x 1440p: 50, 60 1920 x 1440p: 50, 60 1920 x 1200p: 50, 60 1600 x 1200p: 50, 60 1440 x 1080p: 50 60 1440 x 900p: 50, 60 800 x 600p: 50, 60 640 x 480p: 60 SD: 525i: 59.94 NTSC 625i: 50 PAL

Audio Sample Rate	24-Bit, 48 kHz
Supported Codecs	AVC-Intra, AVCHD, Canon XF MPEG2, Digital SLR, DV-NTSC, DV-PAL, DVCPRO50, DVCPROHD, DPX, HDV, XDCAM EX, XDCAM HD, XDCAM HD422, DNxHR, DNxHD, Apple ProRes 4444, Apple ProRes 422 HQ, Apple ProRes 422, Apple ProRes LT, Apple ProRes 422 Proxy, Uncompressed 8-Bit 4:2:2, Uncompressed 10-Bit 4:2:2
Color Space	Rec. 601, Rec. 709, Rec. 2020 Deep Color and HDR Supported
HDMI Video Sampling	8-, 10-, and 12-Bit RGB 4:4:4 (In All Modes up to 4K30) 8- and 10-Bit YUV 4:2:2 and 4:2:0 (In All Modes) 8-Bit RGB 4:4:4 (Supported in All DVI Modes)
HDMI Copy Protection	Compliant
Power Consumption	23 W
Certifications	FCC, CE, RCM, and KC
Operating Temperature	41 to 104°F / 5 to 40°C
Storage Temperature	-4 to 113°F / -20 to 45°C
Relative Humidity (non-condensing)	0 to 90%
Length	4.3" / 10.9 cm

Weight

4.5 oz / 128 g

Packaging Info

Package Weight

0.4 lb

Box Dimensions (LxWxH)

6 x 5.5 x 1"
