

I/O	4 x Bi-directional SDI BNC 1 x Sync BNC input
Interface	PCI-E x4
Format Support	1080p23.98/24/25/29.97/30/50/59.94/60 1080PsF23.98/24/25/29.97/30 1080i50/59.94/60 720p50/59.94 NTSC PAL
SDI Compliance	SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 372M, SMPTE 425M A/B
Sampling	Video: 4:2:2, 4:4:4 Audio: 24-bit, 48 kHz
Color Precision	8, 10-bit YUV 4:2:2 8, 10, 12-bit RGB 4:4:4
Color Space	REC 601, REC 709
OS Compatibility	Mac OS 10.9, 10.10, 10.11 or newer Microsoft Windows 7, 8, 10 Linux
Certification	FCC, CE, C-Tick
Environmental	Operating temperature: 32 to 104°F / 5 to 40°C Storage temperature: -4 to 113° F / -20 to 45°C Relative humidity: 0 to 90% non-condensing
Form Factor	Length: 3.7" / 94 mm Form factor: Single slot

---

Weight	5.6 oz / 160 g
--------	----------------

---

## Packaging Info

---

Package Weight	0.54 lb
----------------	---------

---

Box Dimensions (LxWxH)	5.65 x 5.55 x 1.2"
------------------------	--------------------

---