

I/O 1 x BNC, SD/HD/3G/6G-SDI output
1 x HDMI Type A, v2.0 output

Computer Interface PCI-E 2.0 x4

Codec Support AVC-Intra
AVCHD
Canon XF (MPEG-2)
H.264
DV
DVCPRO50
DVCPROHD
DPX
HDV
XDCAM EX/HD/HD422
Apple ProRes 4444/422
HQ/422/LT/Proxy
Uncompressed 8-bit 4:2:2
Uncompressed 10-bit 4:2:2

Resolution Support 4096 x 2160 23.98/24/25
3840 x 2160 23.98/24/25/29.97/30
1080p
23.98/24/25/29.97/30/50/59.94/60
1080PsF 23.98/24/25/29.97/30
1080i 50/59.94/60
720p 50/59.94/60
NTSC
PAL

SDI Compliance SMPTE 259M, 292M

Audio Sampling 24-bit, 48 kHz

Video Sampling 4:2:2

Color Precision 10-bit

Color Spaces Supported REC 601, REC 709, REC 2020

Operating System Support	MacOS 10.10 or later Windows 7/8.1/10 (64-bit) Linux
Certification	FCC, CE and C-Tick
Environmental	Operating Temperature: 32 to 104°F / 5 to 40°C Storage Temperature: -4 to 113°F / -20 to 45°C Humidity: 0-90%, non-condensing
Dimensions	Length: 4.7" / 119 mm Form Factor: Half-height, half-length Width: Single-slot
Weight	3.2 oz / 90 g

Packaging Info

Package Weight	0.37 lb
Box Dimensions (LxWxH)	5.45 x 5.35 x 1.1"