

I/O	1 x BNC, SD/HD/3G/6G-SDI input 1 x HDMI Type A, v2.0 input
Computer Interface	PCI-E 2.0 x4
Codec Support	AVC-Intra AVCHD Canon XF (MPEG-2) H.264 DV DVCPRO50 DVCPROHD DPX HDV XDCAM EX/HD/HD422 Apple ProRes 4444/422 HQ/422/LT/Proxy Uncompressed 8-bit 4:2:2 Uncompressed 10-bit 4:2:2
Resolution Support	4096 x 2160 23.98/24/25 3840 x 2160 23.98/24/25/29.97/30 1080p 23.98/24/25/29.97/30/50/59.94/60 1080PsF 23.98/24/25/29.97/30 1080i 50/59.94/60 720p 50/59.94/60 NTSC PAL
SDI Compliance	SMPTE 259M, 292M
SDI Metadata Support	VITC read for 3:2 pulldown removal VANC capture using up to 3 lines of video in file HD RP188 and closed captioning
Audio Sampling	24-bit, 48 kHz
Video Sampling	4:2:2

Color Precision	10-bit
Color Spaces Supported	REC 601, REC 709, REC 2020
Operating System Support	MacOS 10.10 or later Windows 7/8.1/10 (64-bit) Linux
Certification	FCC, CE and C-Tick
Environmental	Operating Temperature: 32 to 104°F / 5 to 40°C Storage Temperature: -4 to 113°F / -20 to 45°C Humidity: 0-90%, non-condensing
Dimensions	Length: 4.7" / 119 mm Form Factor: Half-height, half-length Width: Single-slot
Weight	3.2 oz / 90 g

## Packaging Info

---

Package Weight	0.4 lb
Box Dimensions (LxWxH)	5.4 x 5.3 x 1.2"