

Inputs	1 x BNC, SD/HD/3G-SDI 1 x 3BNC, component/composite analog video 1 x BNC, Reference Input for Tri-Sync or Black Burst 2 x 1/4" TS, analog audio
Outputs	2 x BNC, SD/HD/3G-SDI 1 x HDMI Type A
Other I/O	1 x DB-9, RS-422 1 x USB Type-C, Thunderbolt 3.0
Resolution Support	2048 x 1080 23.98/24/25 2048 x 1080PsF 23.98/24/25 1080p 23.98/24/25/29.97/30/50/59.94/60 1080PsF 23.98/24/25/29.97/30 1080i 50/59.94/60 720p 50/59.94/60 NTSC PAL
Embedded Audio	Input: 16 channels via SDI Output: 16 channels via SDI, 2 channels via HDMI
SDI Compliance	SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 372M, SMPTE 425M A/B
SDI Video Sampling	8/10/12-bit, 4:2:2, 4:4:4 (12-bit and 4:4:4 sampling not supported above 1080p30)
Audio Sampling	24-bit, 48 kHz
SDI Metadata Support	RP 188/SMPTE 12M-2 and closed captioning

Color Space	REC 601, REC 709
Operating System Support	Apple Mac OS X 10.11 El Capitan or later Microsoft Windows 7/8.1/10 (64-bit only) Linux
Environmental	Operating Temperature: 32 to 104°F / 5 to 40°C Storage Temperature: -4 to 113°F / -20 to 45°C Humidity: 0-90%, non-condensing
Dimensions	5.5 x 6.7 x 1.75" / 14 x 17 x 4.4 cm
Weight	1.3 lb / 544 g

Packaging Info

Package Weight	1.84 lb
Box Dimensions (LxWxH)	9.05 x 7.85 x 2.3"