

# **Adder DDX30-US Flexible 30-Port KVM Matrix Switch for DVI/DisplayPort/VGA/USB and Audio**

## **System connections**

30 x 8p8c ports for computer or user connections (7 front panel ports are dedicated for users).

Maximum of 23 computer connections, minimum of 1 computer.

Maximum of 29 user connections, minimum of 7 users.

## **Peripheral connections**

1 x 8p8c for 10/100/1000 Ethernet connection. 1 x 9way D-type RS232 options port.

## **Power**

2 x locking 3-pin jack (1 x power adapter included), 100-240VAC 50/60Hz, 0.7A, input to power adapter, 12VDC 18W output from power adapter.

## **Physical design**

Compact case, robust metal construction. Designed for 19 inch rack mounting:

435mm/17.13" (w), 31mm/1.22" (h), 160mm/6.3" (d), 1.9kg/ 4.2lbs.

## **Operating temperature**

0 to 40°C / 32 to 104°F.

## **Approvals**

CE, FCC.

## **Local client requirements**

Any of the following:

Internet Explorer® version 10 or 11.

Firefox version 24 ESR and above.

Chrome version 43.

## **Important extension distance details**

A minimum specification of Shielded Twisted Pair (STP) cables must be used with the DDX30, DDX10, DDX CAM and DDX USR.

Recommended cables are SFTP:

Daetwyler 7702 Flexible patch cable

Daetwyler 7120 Bulk cable