

# OWI AMP6022B 2 Way 6.5 inch Amplified Black Speaker and 4 Ohms 6 inch 2-way Black Surface Mount Speaker

## AMP602

DESCRIPTION:	6.5" active
OUTDOOR:	NO
IMPEDANCE:	40
DISPERSION	92°
SENSITIVITY (1W/1M):	83 dB (VR at MAX)
POWER:	15W x 2
FREQUENCY RESPONSE:	80 Hz - 20 kHz
CROSS OVER:	3.5 K
S/N:	>80 dB
INPUT CONFIGURATION:	RCA L/R
INPUT LOAD IMPEDANCE:	20 KO
MAXIMUM CURRENT PROTECTED:	YES
ONE WIRE TO GROUND PROTECTED:	YES
SHORT CIRCUIT PROTECTED:	YES
THD:	<0.2%
POWER SUPPLY:	115V
HIGH FREQUENCY DRIVER:	1.5 kHz-20 kHz
LOW FREQUENCY DRIVER:	80 Hz - 6 kHz
WOOFER SIZE:	6.5"
WOOFER MATERIAL:	Mica
TWEETER SIZE:	.79" (20 mm)
TWEETER MATERIAL:	PEI
ENCLOSURE:	High Impact Polystyrene (HIPS)

## P602

DESCRIPTION:	6.5" Passive Cabinet Speaker
OUTDOOR:	NO
IMPEDANCE:	4Ω
DISPERSION	92°
SENSITIVITY (1W/1M):	86 dB
MAX POWER:	30 W
NOMINAL POWER:	15 W
FREQUENCY RESPONSE:	80 Hz - 20 kHz
CROSSOVER:	6 dB
HIGH FREQUENCY DRIVER	1.5 kHz-6 kHz
LOW FREQUENCY DRIVER	80 Hz - 6 kHz
WOOFER SIZE:	6.5"
WOOFER MATERIAL:	Mica / Foam Surround
TWEETER SIZE:	.79" (20 mm)
TWEETER MATERIAL:	PEI
ENCLOSURE:	Plastic Enclosure
CE APPROVED:	Yes
WEIGHT(pounds/kgs):	10 lbs. / 4.5 kgs
PAINTABLE:	Yes
WARRANTY:	1 Year