

Ashly TM-335 35-W 3-Input Mixer/Amplifier with XFMR Isolated Constant-Voltage/4 Ohm Out

Specifications Note: 0dBV = 1V	
Channels	3
Signal to Noise (26dB Gain)	89dB
Output Power: 5% THD	
4 Ohms, 8 Ohms, 25V, 70V	35W
line Current Draw: @ 120VAC 60Hz (Divide values by 2 for 230VAC)	
Standby Mode	0.11A
Typical (1/8 power pink noise)	0.27A
Max (1/3 power sine wave)	0.31A
Thermal Dissipation: BTU/hr	
Standby Mode	3D
Typical (1/8 power pink noise)	68
Max (1/3 power sine wave)	75

General	
Operating Temp	-10°C~t40°C
Tone Control	Bass (100Hz) i10dB, Treble (10kHz) i10dB
Input Sensitivity	-50dBV/600OhmsMic 1,2,3) -15dBV / 10k Ohms (Aux, CD/Satellite)
Frequency Response (+0,-3dB)	130Hz-20kHz (Mk1,2,3) 50Hz-20kHz (Aux, CD/Satellite) 330Hz-3kHz (Telephone)
THD	<5%(35W@1KHz)
Dimensions	11.4"Wx3"Hx7.3"D (290mm x 76mm x 185mm)
Unit Weight	8.7lbs (3.95kg)
Shipping Weight	11lbs(5kg)
Power Requirements*	100-120VAC, 50/60Hzor 220-240VAC, 50/60HZ