

OWI AMPLV6022B 6.5 inch Low voltage amplified Black Speaker and 6 inch 2-way Black Surface Mount Speaker

AMPLV602

DESCRIPTION:	1 each 6.5", 2-Way, Surface Mount Amplified Speaker and 1 each Non- amplified Speaker
OUTDOOR:	No
IMPEDANCE:	4Ω
DISPERSION	92°
SENSITIVITY (1W/1M):	83 dB (VR at Max)
POWER:	15 W x 2
FREQUENCY RESPONSE:	80 Hz - 20 kHz
S/N:	>80dB
INPUT CONFIGURATION:	RCA UR
INPUT LOAD IMPEDANCE:	20 KΩ
MAXIMUM CURRENT PROTECTED:	Yes
ONE WIRE TO GROUND PROTECTED:	Yes
SHORT CIRCUIT PROTECTED:	Yes
THD:	<0.2%
POWER SUPPLY:	15V DC, UL Listed, Level 5 (Energy Star)
HIGH FREQUENCY DRIVER:	1.5 kHz-20 kHz
LOW FREQUENCY DRIVER:	80 Hz - 6 kHz
WOOFER SIZE:	6.5"
WOOFER MATERIAL:	Mica
TWEETER SIZE:	0.79"(20 mm)
TWEETER MATERIAL:	PEI
ENCLOSURE:	High Impact Polystyrene (HIPS)
WEIGHT:	12 lbs. (5.5 Kgs)
PAINTABLE:	Yes

P602

DESCRIPTION:	6.5" Passive Cabinet Speaker
OUTDOOR:	NO
IMPEDANCE:	4Ω
DISPERSION	92°
SENSITIVITY (1W/1M):	86 dB
MAX POWER:	30 W
NOMINAL POWER:	15 W
FREQUENCY RESPONSE:	80 Hz - 20 kHz
CROSSOVER:	6 dB
HIGH FREQUENCY DRIVER	1.5 kHz-6 kHz
LOW FREQUENCY DRIVER	80 Hz - 6 kHz
WOOFER SIZE:	6.5"
WOOFER MATERIAL:	Mica / Foam Surround
TWEETER SIZE:	.79" (20 mm)
TWEETER MATERIAL:	PEI
ENCLOSURE:	Plastic Enclosure
CE APPROVED:	Yes
WEIGHT(pounds/kgs):	10 lbs. / 4.5 kgs
PAINTABLE:	Yes
WARRANTY:	1 Year