

Digital Projection E-Vision LASER 6500 Projector/WUXGA 6500/5000x1 /1920x1200

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
HDMI 1.4b	HDMI	2	3D Sync Out	BNC	1
DVI-D	DVI	1	3D Sync In	BNC	1
VGA / Analog RGB	15-pin D-Sub	1	LAN	RJ45	1
Component Video	5 x BNC	5	Serial In (RS232)	9-pin D-Sub	1
HDBaseT	RJ45	1	Serial Out (RS232)	9-pin D-Sub	1
Video Out: VGA	15-pin D-Sub	1	Wired Remote In	3.5mm Stereo Jack	1
Audio In: Stereo	RCA	2	Wired Remote Out	3.5mm Stereo Jack	1
Audio In: Stereo	3.5mm Jack	1	12V Trigger	3.5mm Stereo Jack	1
Audio Out: Stereo	RCA	2	USB (power only)	USB Type A	1
			USB (Service)	USB Type B	1

3D Formats Supported	HDTV Formats Supported
Frame Packing	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz), 1080i (50Hz, 60Hz), 720p (50, 60Hz)
Side By Side (half)	
Top and Bottom	
Computer Compatibility	Bandwidth
Up to 1920 x 1200	165 MHz on analog RGB
	165 Megapixels per second on HDMI
Remote Control	Automation Control
IR remote control, wireless and wired	Crestron RoomView® Connected
On-Board keypad	PJLink - AMX SSDP
	LAN
	RS232 - AMX SSDP
Lamp Type	Typical Lamp Life
Laser Light Source	20,000 hours

Lenses			
Lens	Part No.	Focus Range	Lens Shift
0.77: 1 fixed	114-785	0.4m - 3.1m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
1.1 - 1.3: 1 zoom	116-207	1m - 9m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
1.54 - 1.93: 1 zoom	114-783	0.95m - 11.9m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
1.93 - 2.91: 1 zoom	114-784	1.2m - 29.8m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
3.0 - 5.0: 1 zoom	116-208	3m - 20m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
Lens Mount			
Manual shift, zoom & focus.			

Mechanical Mounting	
Front/Rear Table	
Front/Rear Ceiling	
Adjustable Front/Rear Feet	
Power Requirements	Power Consumption
100-240 VAC, 50/60HZ	650W
Thermal Dissipation	Fan Noise
1807 BTU/Hour	33 dBA
Operating/Storage Temperature	Operating Humidity

Operating: 0 to 40C (32 to 104F) Storage: -20 to 60C (-4 to 140F)	10 to 85% non-condensing
Weight (Chassis Only)	Dimensions
25 kg 55.1 lb	L: 47.0 cm W: 51.7 cm H: 22.5 cm L: 18.5 in W: 20.4 in H: 8.9 in