

## OWI ICM6730SET 6-inch 25/70/100 Volts In-Ceiling Speaker with Built-In Tile Bridge and Backcan/55Hz-20kHz

DESCRIPTION:	6.5" 2-Way Poly Coated Woofer Swivel Tweeter
COVERED OUTDOOR:	Yes
IMPEDANCE:	8 Ohms
70 VOLT TAPS:	1.75W, 3.5W, 7W, 15W, 30W
100 VOLT TAPSS:	3.5W, 7W, 15W, 30W
8 OHMS TAPSS:	60W
SENSITIVITY (1W/1M):	86 dB
MAX POWER:	120 Watts
NOM. POWER:	60 Watts
FREQUENCY RESPONSE:	55 Hz - 20 kHz
CROSSOVER:	4.2 kHz
INPUT CONNECTION:	Phoenix Connector
WOOFER SIZE:	6.5"
WOOFER MATERIAL:	Poly Coated
TWEETER SIZE:	1"
TWEETER MATERIAL:	PEI
ENCLOSURE:	Built-in Metal Backcan
GRILL MATERIAL:	Aluminum
DIMENSIONS	8" x 10" x 10"
MASTER CARTON DIMENSIONS (LxWxH):	30" x 24" x 13"
MASTER CARTON QUANTITY:	2 pairs
CUTOUT SIZE:	8 3/4" Diameter
WEIGHT:	11 lbs.
MOUNTING HARDWARE:	Kwik Klamps
MOUNTING BRACKET:	T-Bar (included)
PAINTABLE:	Yes
OUTDOOR RATED:	No
COVERED OUTDOOR:	Yes