

**OWI ICM8 (EACH) 8-inch 25/70/100 Volts 8 Ohms In-Ceiling Speaker (Each) with Backcan and T-bar Bracket**

Description:	Full Range, 8" InCeiling 25V/70V/100V 100W Switchable SUB/HC
Impedance:	8Q or 25V/70V/100V
25 Volt Taps:	13W, 6.3W, 3.1 W, & 1.6W
70 Volt Taps:	100W, 50W.25W, &13W
100 Volt Taps:	100W, 50W, &25W
8 Ohms Tap	YES
Sensitivity (1W/1M):	91dB
Max Power:	200W
Nominal Power:	100W
Frequency Response:	80Hz - 17KHz (-3dB) / 55Hz - 20KHz (-10dB)
Crossover:	Full Range(1.8KHz) / 125Hz / 6KHz
Dispersion (Coverage):	112°
Input Connection:	Removable locking connector with screw-down terminals. 2 input terminals and 2 loop-thru output terminals. Max. wire 12 AWG (2.5 mm2)
Woofer Size:	8" Dia.
Woofer Material:	Paper Cone-Coated
Tweeter Size:	1" Dia.
Tweeter Material:	Silk Dome Tweeter
Grill Material:	Aluminum
Dimensions (HxWxD)	11" x 13" x 13"
Cut Out Size:	11 3/4"
Mounting Hardware:	YES
Mounting Bracket: (Included)	YES
Paintable:	YES
Outdoor rated:	NO
Covered Outdoor:	Yes