

Soundtube RS42-EZ-BK 4in Open-Ceiling Speaker/16 Ohm/140 Hz - 22 kHz/Black

System Type	4.0" Coax, open-ceiling, ported (20 Watt transformer for 25/70.7/100 Volt or voice coil direct)
Impedance (nominal) ¹	16 ohm
Sensitivity dB @ 2.83 V/1 m	84.0 dB
Sensitivity dB @ 1 W/1 m ²	87.0 dB
Frequency Response (- 3 dB) ³	140 Hz-22 kHz
Frequency Response (- 10 dB) ³	100 Hz - 22 kHz
Max. Program Power ⁴	40 W
Max. Continuous Power RMS ⁵	20 W
Max. Power SPL @ 1 m ⁶	100.0 dB
Tap Selector	6 Position rotary switch with transformer bypass
Transducer - Low Frequency Driver	102mm (4in) Polypropylene cone, butyl rubber surround
Transducer- High Frequency Driver	19mm (0.75in) Silk dome with Beam Ring™
Low Frequency Voice Coil	25.4 mm (1.00 in)
Crossover Frequency	4.5 kHz
Network Type: Low Pass	12dB per octave, 2nd order
Network Type: High Pass	6dB per octave, 1 st order
Enclosure Material	Injection molded ABS. glass fiber reinforced
Grille	Powder coated aluminum
Inputs	4 position ceramic terminal connector
Colors	Black or white (paintable)
Height	199.6 mm (7.86 in.)
Diameter	189.5 mm (7.46 in.)
Weight	1.8 kg (3.9 lbs.)
Shipping Weight	2.7 kg (6 lbs.)
Packaging	One per box
Included Accessories	Hanging hardware, weather plug, cover plate
Optional Accessories	N/A
Regulatory - UL	UL 1480 UEAY & UL 2239 Listed
Regulatory - CE	Approved
RoHS	Approved