

Soundtube IPD-RS62-EZ-BK 6.5 inch Coax Open-Ceiling Network Speaker/Black

Frequency Response (± 3 dB)	100 Hz-20 Hz
Frequency Response (± 10 dB)	80 Hz - 22 kHz
Max. Power SPL @ 1 M	101. dB
Directivity Factor (Q) (Averaged 100Hz - 10kHz, <3> 2kHz)	3.6 (Average 100 Hz - 10 kHz) 7.1 (2 kHz)
Directivity Index (DI) dB (Averaged 100Hz - 10kHz, (5) 2kHz)	5.5dB (Average 100 Hz -10 kHz) 8.5dB (2 kHz)
Total Bi-Amp Power	40 W
Color	Black
Connections	RJ45 ethemet connector
Height (SM = Height)	264.2 mm /10.4 in
Diameter (SM = Width)	256.0 mm /10.08 in
Weight	3.2 kg / 7.0 lbs
Shipping Weight	4.1 kg/9.0 lbs
Accessories Optional	Beam Clamp (AC-BC-1), Split Loom Tubing (AC-SLT-10),Hanging Kit (AC-RSEZ-HH-10),Hanging Kit (AC-RSEZ-HH-20),50' Hanging Kit (AC-RSEZ-HH-50),-Forged Eyebolt (AC-FEI),Snap Link (AC-SL-1)