

Soundtube RS62-EZ-WH 6.5in Open-Ceiling Speaker/16 Ohm/100 Hz - 22 kHz/White

System Type	6.5" Coax, open-ceiling, ported (32 Watt transformer for 25/70.7/100 Volt or voice coil direct)
Impedance (nominal) ¹	16 ohm
Sensitivity dB @ 2.83 V/1 m	86.0 dB
Sensitivity dB @ 1 W/1 m ²	89.0 dB
Frequency Response (- 3 dB) ³	100 Hz - 22 kHz
Frequency Response (- 10 dB) ³	80 Hz - 22 kHz
Max. Program Power ⁴	64 W
Max. Continuous Power RMS ⁵	32 W
Max. Power SPL @ 1 m ⁶	104.0 dB
Tap Selector	6 Position rotary switch with transformer bypass
Transducer - Low Frequency Driver	165 mm (6.5 in.) Polypropylene cone, butyl rubber surround
Transducer- High Frequency Driver	25.4 mm {1.00 in} Silk dome with Beam Ring™
Low Frequency Voice Coil	25.4 mm (1.00 in)
Crossover Frequency	3.0 kHz
Network Type: Low Pass	6dB per octave, 1 st order
Network Type: High Pass	6dB per octave, 1 st order
Enclosure Material	Injection molded ABS. glass fiber reinforced
Grille	Powder coated aluminum
Inputs	4 position ceramic terminal connector
Colors	Black or white (paintable)
Height	264.2 mm (10.4 in.)
Diameter	256.0 mm (10.08 in.)
Weight	3.2 kg (7.0 lbs.)
Shipping Weight	4.1 kg (9.0 lbs.)
Packaging	One per box
Included Accessories	Hanging hardware, weather plug, cover plate
Optional Accessories	N/A
Regulatory - UL	UL 1480 UEAY & UL 2239 Listed
Regulatory - CE	Approved
RoHS	Approved