

Soundtube XT550-SS 5.25-in COAXIAL OUTDOOR SPEAKER/Sand stone

System Type	5.25" coaxial outdoor (32 Watt transformer for 25/70.7/100 Volt or 4 Ohm transformer bypass position)
Impedance (nominal)	4 Ohms (nominal)
Sensitivity dB @ 2.38 V/1 m3	86 dB
Sensitivity dB @ 1W/1m	83 dB
Frequency Response (-3 dB)1	61 Hz-9.5 kHz port open (101 Hz -12 kHz port closed)
Frequency Response (-10 dB)1	49 Hz - 22 kHz port open (62 Hz - 22 kHz port closed)
Max. Program Power	120 Watts
Max. Continuous Power RMS2	60 Watts
Max. SPL dB @ 1 M	101 dB
Coverage Angle (-6 dB @ 2 kHz)	360° Horizontal - 40° Vertical
Coverage Angle (-6 dB @ 10 kHz)	360° Horizontal - 40° Vertical
Tap Selector	5-Posrtbn rotary switch with transformer bypass position
Transducer- Low-Frequency Driver	1 x 133 mm (5.25 in) Polypropylene cone, butyl rubber surround
Transducer- High-Frequency Driver	1 x 25 mm (1.0 in) Aluminum dome
Low-Frequency Voice Coil	25 mm (1.0 in)
Network Type- Low Pass	6 dB per octave, 1 st order
Network Type- High Pass	6 db per octave, 1 st order
Crossover Frequency	3.0 kHz
Enclosure Material	Roto-molded polyethylene plastic
Grille	Stainless-steel with powder-coat finish
Inputs	18-Gauge wire lead
Color Options	Granite green or sandstone
Diameter	360 mm (14.17 in)
Total Height	394 mm (15.51 in)
Weight	5.9 kG (13.0 lbs)
Shipping Weight	8.6 kG (19.0 lbs)
Included Accessories	Anti-theft brackets, water-tight strain relief
Optional Accessories	N/A
Packaging	1 Per box
Regulatory- UL	1480 (UEAY) pending
Regulatory- CE	Approved
Regulatory- IP	IP55 Approved
RoHS	Approved