

Adder X2-DA-SILVER-US KVM/RS232 Dual Access Extender (Transmitter/Receiver) up to 300m (1000ft)

Video resolutions

1600x1200 at distances up to 200m (650ft) 1280x1024 at distances up to 300m (1000ft)

Extension distance

Up to 300 metres/1000ft using CATx cable (x=5,5e,6,7)

Devices supported

Supports PS/2 style keyboard, PS/2 style mouse, flat-screen and CRT style monitors with standard HD-15 video connectors. Transparent RS232 connection.

O/S compatibility

All known software and operating systems including Windows (all), DOS, Linux, Unix, BSD, Sun OS, Solaris, Mac OS, NetWare etc.

Connectors (Local computer-end unit)

Computer connection: 1 x 25-way female connector (cable supplied)

Local console connection (DA only)

video HDD15, keyboard/mouse: MiniDin6. CATx: 1 x RJ45 connector. Serial: DB9. Optional power: 2.5mm DC jack

Connectors (Remote console-end unit)

Video: HDD15. Keyboard/Mouse: MiniDin6. CATx: 1 x RJ45 connector. Serial: DB9. Power: 2.5mm DC jack

Physical (Tx and Rx units)

172mm x 26mm x 75mm, 430g, fits into one slot width in the X-Series rack mount chassis (16 units fit into 2U of rack space)

Power supply

100-240VAC, 50-60Hz

Operating temperature

0 - 40 deg C (32 to 104 deg F)

Approvals

CE, FCC