

Barco R9004776 EX Video Processor Event Master expansion unit

Video inputs	Two card slots which can be either input or output <ul style="list-style-type: none"><li>Up to 8 inputs using any of the Event Master input cards</li><li>Inputs can be distributed to other processors via the link cable or to a locally installed output card</li></ul>
Video outputs	Two card slots which can be either input or output <ul style="list-style-type: none"><li>Up to 8 outputs using any of the Event Master output cards</li><li>Sources for the outputs can be from remote systems via the link connection or from a locally installed input card.</li></ul>
Genlock	Analog reference input on BNC connectors; Blackburst and Bi-level at SD, and Tri-level at HD Reference output is provided by an internal sync generator capable of Bi- level and Tri-level sync signals
Program output	Up to 8 program outputs for destinations created in a linked E2 or S3-4K processor.
Scaled Aux outputs	User definable up to 8 x 2048x1200@60 or 2 x 4K@60
Mixers	N/A
Still stores	Up to 100 HD stills available in Aux
Layer effects	N/A
Multiviewer	Ex inputs and outputs can be viewed in the host E2 or S3-4K processor Multiviewer, just as if the inputs and AUX outputs resided in the host processor.
Expandability	<ul style="list-style-type: none"><li>Easily expandable for larger display applications via proprietary links</li><li>Link units to increase available inputs and outputs for larger tiled/ blended widescreen applications</li><li>Two Ex chassis can be linked for standalone operation</li><li>S3-4K supports up to 4 Ex chassis linked (16 inputs and 16 outputs of HD video)</li><li>E2 supports up to 8 Ex chassis linked. (32 inputs and 32 outputs of HD video)</li></ul>
HDCP	HDCP compliant
Control	<ul style="list-style-type: none"><li>Event Master screen management software for PC or MAC</li><li>Ethernet RJ-45, 1000/100/10 Mbps autosense</li></ul>
Serviceability	Field-Serviceable I/O cards (not hot-swappable)
Dimensions	<ul style="list-style-type: none"><li>Height: 4.37 cm (1.72 in)</li><li>Width: 48.26 cm (19 in)</li><li>Depth: 40.41 cm (15.91 in)</li></ul>
Weight	5.53 kg / 12.2 lbs
Power	Input power: 100-240 VAC 50/60Hz 125W
Environmental temperature	0-40° C / 32-104 F
Environmental humidity	0-95% non-condensing
Warranty	3 years parts and labor