

# **Adder X200AS/R-US KVM/USB Extender (Receiver) with Audio and Speaker connectors up to 300m/1000ft**

## **Video Resolution**

1920 x 1200 at distances up to 50 m/165 ft, 1600 x 1200 at distances up to 200 m/650 ft, 1280 x 1024 at distances up to 300 m/1000 ft.

## **Extension Distance**

Up to 300 m/1000 ft. using CATx cable (x=5,5e,6)

## **Devices Supported**

Supports computers with USB style keyboard and mice, flat-screen and CRT style monitors with standard HDD-15 video connectors and optional audio through 3.5 mm audio jack.

## **O/S Compatability**

All known software and operating systems including Windows (all), DOS, Linux, Unix, BSD, Sun OS, Solaris, Mac OS, NetWare etc.

## **Connectors (USB CAM)**

Video: HDD-15 Optional audio: 3.5 mm jack Keyboard, Mouse: USB type A CATx: RJ45 connector

## **Connectors (X200 remote unit)**

Video: HDD-15 Optional audio: 3.5 mm jack Keyboard, Mouse: USB Type A CATx: 2 x RJ45 connector Power: 2.5 mm DC jack

## **Physical (USB CAM)**

Combination of plastic enclosure and cables. Enclosure: 64 mm/2.5 in. x 45 mm/1.8 in. x 25 mm/1 in. Cables: 340 mm/13.4 in. long

## **Physical (X200 remote unit)**

All metal case, 172 mm/6.8 in. x 26 mm/1 in. x 75 mm/3 in. 430 g/1 lb.

## **Power Supply**

100 - 240VAC 50/60Hz (X200 remote unit only)

## **Order Codes Remote unit only (X200)**

X200/R-XX (100 m/330 ft, no audio/de-skew) X200A/R-XX (100 m/330 ft, audio, no de-skew) X200AS/R-XX (300 m/1000 ft, audio/de-skew)

## **Remote unit (X200) with CAM (computer access module)**

X200-USB/P-XX (X200 USB receiver with CATX-USB computer access module) X200A-USB/P-XX (X200A USB receiver with CATX-USBA computer access module) X200AS-USB/P-XX (X200AS USB receiver with CATX-USBA computer access module)

XX= Mains Lead Country Code: UK = United Kingdom US = United States EURO = Europe AUS = Australia