

Color	White
UPC	752830440180
Manufacturer	SoundTube
Manufacturer's Category	CM-EZ Economical In-Ceilings
Carton Height	17.5 in / 444.5 mm
Carton Length	16.5 in / 419.1 mm
Carton Width	15.25 in / 387.35 mm
Enclosure Properties	ABS Glass Fiber Reinforced, Injection Molded, Sealed
Enclosure Volume	60 cu in / 983.22 cu cm
Included Accessories	Conduit Clamp, Grille, Paint Mask, Tile Bridge, Wire Nuts
Optional Accessories	White Grille (GRL-CM31-WH) Tile Bridge (AC-CM31-TB) Pre-Construction Bracket (AC-CM31-PCB) Junction Box (Included with pre-construction bracket)
Source Inputs	Wire Leads
Shipping Weight	31 lbs / 14.06 kg
Backcan Diameter	5.5 in / 139.7 mm
Backcan Height	3.5 in / 88.9 mm
Coverage Angle (-6dB @ 2kHz)	45°
Cutout Width/Diameter	5.5 in / 139.7 mm
Directivity Factor (Q) (Averaged 100Hz - 10kHz, @ 2kHz)	4.5 and 3.5
Directivity Index (DI) dB (Averaged 100Hz - 10kHz, @ 2kHz)	5.3dB and 5.2dB
Frequency Response (± 10 dB)	115 Hz - 22 kHz
Frequency Response (± 3 dB)	190 Hz - 14 kHz
Grille Properties	Aluminum, Standard-Flange, Powder-Coated, White, Snap-Fit
Low Frequency Voice Coil	0.75 in / 19 mm
Magnetically Boosted	No
Max. Ceiling Thickness	1.5 in / 38.1 mm

Max. Continuous Power RMS	20W
Max. Program Power	40 W
Minimum Impedance (Ω Ohms)	8 Ω
Minimum Ceiling Thickness	0.1 in / 2.5 mm
Nominal Impedance (Ω Ohms)	8 Ω
Fullrange Driver	3" Polypropylene driver with butyl rubber surround
Sensitivity dB @ 1W/1M	85 dB
Sensitivity dB @ 2.83V/1M	85 dB
Tap Selector	Rotary Switch
Transformer Options	25 / 70.7 / 100 V, 8 Ohm direct
Transformer Taps (25V/70.0V/100V)	1.3W/10W/30W
Visible Diameter	6.3 in / 160 mm
Visible Height	0.6 in / 15.2 mm