

Apantac Mi-9# 9x2 Cost-Effective Compact Video Multiviewer/2x HDMI/SDI Outputs

VIDEO INPUTS	9 3G SDI Level A&B, HD/SD-SDI	OUTPUTS	2 independent HDMI and SDI outputs
TOTAL WINDOWS	9	OUTPUT RESOLUTION	1920 x 1080p 50/60Hz
CONNECTORS	HD-BNC	AUDIO OUTPUTS	Embedded HDMI and SDI Audio
SERIAL DIGITAL	SMPTE 424M, 292M, 259M	ON-SCREEN DISPLAY	Borders, labels, tally UMD, OMD, IMD, dynamic UMD
EQUALIZATION	120m at 2.97 Gbps, 140m at 1.48 Gbps, 400m at 270 Mbps with Belden 1694A	GENERAL PURPOSE I/O	9 inputs with RJ50 - DB9 connectors
RETURN LOSS	> 15db up to 1.485 Gbps > 10db up to 3G	SERIAL PORT	N/A
EMBEDDED AUDIO	SMPTE-272M-A	IP	100 Base-Tx, TSL, AXP Connector: RJ45
ALARMS	No audio, audio high/low, no video, video format display	ELECTRICAL	15W
EMI/RFI	Complies with FCC Part 15 Class A, CE, EU EMC, C-tick		