BZBGEAR BG-AUD-TCS Long Range Digital/Analog Audio Extender Kit over Cat5e/6/7 up to 950ft (Stereo/TOSLINK/COAX)

Transmitter	Input: TOSLINK, COAX or AUDIO Output: TP OUT
Receiver	Input: TP IN Output: TOSLINK, COAX & RCA (L+R)
General	
Audio Format	TOSLINK & COAX: PCM/Dolby/DTS; AUDIO: Stereo
Sound Channel	TOSLINK & COAX: 2.0-7.1
Frequency Response	20 Hz to 20 kHz, ±3 dB
Sample Rate	TOSLINK & COAX: 48k/96k/192k 16bit/18bit/24bit
Transmission Distance	Stereo: Up to 170m (CAT5e/6/7) TOSLINK/COAX: Up to 290m (CAT5e/6/7)
Power Supply	Input: 100VAC~240VAC, 50/60Hz; Output: 12VDC, 1A
Power Consumption	2.5W (Max)
Work Temperature	14°F ~ 131°F / -10°C ~ +55°C
Humidity	10% ~ 90%
Net Weight	Transmitter: 0.24 lbs [110g]; Receiver: 0.26 lbs [119g]
Dimension (WxHxD)	3.5 x 3.1 x 0.85in [88 x 80 x 21.5mm]