

## INPUTS

**2 HDMI:** On female HDMI connectors

**1 USB-C:** On a female USB-C connector (DP Alternate Mode)

**1 Unbalanced Stereo Audio:** On a 3.5mm mini jack

---

## OUTPUTS

**1 HDMI:** On a female HDMI connector

**1 Balanced Analog Stereo Audio:** On a 5-pin terminal block

---

## PORTS

**4 Contact Closure Switches:** On a 4-pin terminal block

**1 USB:** On a USB-A connector for firmware upgrade

---

## VIDEO

**Max. Input Resolution:** 4K@60 (4:4:4)

**Max. Data Rate:** 18Gbps (6Gbps per graphic channel)

**Latency:** 1–2 frames

**Content Protection:** HDCP 2.2 & 1.4

---

## USER INTERFACE

**Controls:** Input selector, video freeze and resolution reset front panel buttons, OSD menu

**Indicators:** Selected input and power LEDs

---

## POWER

**Source:** 24V DC

**Consumption:** Up to 3.4A (when charging USB-C devices at 60W)

---

## ENCLOSURE

**Size:** MegaTOOLS®

**Type:** Aluminum

**Cooling:** Convection ventilation

---

## ENVIRONMENTAL CONDITIONS

**Operating Temperature:** 0° to +40°C (32° to 104°F)

**Storage Temperature:** –40° to +70°C (–40° to 158°F)

**Humidity:** 10% to 90%, RHL non-condensing

---

## ACCESSORIES

**Included:** Power adapter, bracket set, rubber feet

---