

<b>Weight Net</b>	29.54lbs (13.4kg)
<b>Depth</b>	12.56" (319mm)
<b>Width</b>	12.99" (330mm)

## SPECIFICATIONS

<b>Height</b>	20.91" (531mm)
<b>Available Color</b>	Black or White
<b>Axial Sensitivity (SPL, 1 W @ 1 m)</b>	90dB
<b>Connector Type</b>	Dual NL4
<b>Coverage (Nominal -6 dB) H</b>	90°
<b>Coverage (Nominal -6 dB) V</b>	60°
<b>Crossover Frequency</b>	2 kHz
<b>Enclosure Material</b>	Polypropylene Composite
<b>Family</b>	ELX200
<b>Frequency Range (-10 dB)</b>	49 Hz - 22 kHz
<b>Frequency Response (-3 dB)</b>	65 Hz - 20 kHz
<b>Grille</b>	18 AWG steel with powdercoat
<b>HF Transducer</b>	DH-1C 1-inch titanium compression driver
<b>LF Transducer</b>	EVS-10M 254 mm (10 in)
<b>Max. SPL/1m (calc)</b>	127dB
<b>Minimum Impedance</b>	7.2Ω
<b>Nominal Impedance</b>	8Ω
<b>Power Handling (Continuous / Peak)</b>	300 W/1200W
<b>Power Rating</b>	1200W
<b>Recommended High-Pass Frequency</b>	55Hz
<b>Shipping Weight</b>	33.73lbs (15.3kg)
<b>Speaker Type</b>	Full-Range
<b>Suspension</b>	(3) M10 suspension points
<b>Woofers Size</b>	10inch