

# Adder ALIF100T-VGA Zero U form factor IP-based VGA/KVM Extender (Transmitter) with USB

## Operating/storage conditions

Operating temperature: 0 to 50°C / 32 to 122°F  
Storage temperature: -10 to 60°C / 14 to 140°F  
Storage and operating relative humidity: 10-90% non-condensing  
Altitude: < 3000m  
MTBF: >500,000 hours

## Power

USB power: 2 x USB2.0 (2x 500mA @5V) 5W  
External power: 5VDC, 1A, (LPS)  
Typical power consumption: 3W  
BTU: 10.2BTU/hr

## Physical

Dimensions: (L)110mm /4.3" x (W)55mm/2.17" x (D)25mm/1" with 30cm cable length  
Weight: 0.2kg /0.4 lb  
Materials: ABS and aluminium construction

## Connectors

Computer: VGA, USB type A x 2  
Ethernet: 1 x 8p8c (RJ45)  
Power: 2.5mm socket

## Specification

USB: USB2.0 full and low speed (No HS support)  
USB features: Keyboard, mouse and touch  
USB device seen as: 7 or 13 port hub  
Max video resolution: Up to 1920x1200@60Hz  
Audio: Line in/out USB audio 2 channel 16bit 48KHz  
DisplayPort Audio: None  
Ethernet: 1GbE (No 10/100 support)

## Packing Box

Dimensions: (L) 292mm /11.5 inch (W) 245mm/9.6inch (D) 55mm/2.1inch  
Weight: 0.5kg / 1.1lb

## Approvals / Compliance

CE and FCC: See the compliance web page for the full list

## Cable types recommendations

Cat5e and above

## Cable length rules

Ethernet specifications rules apply 100 meters maximum run

**Note: If using with an AIM Manager, the AIM must be running firmware version 4.7 or above**