

A-NeuVideo ANI-42HPIPX 4x2 18Gbps 4K60 UHD HDMI Matrix Switcher with PiP

- **HDMI Bandwidth:** 18Gbps
- **Input Ports:** (4) HDMI (Type-A)
- **Output Ports:** (2) HDMI (Type-A)
- **Control Ports:**
 - RS-232 (3.5mm)
 - IP Control (RJ-45)
- **Service Port:** USB 2.0 (Type A)
- **Baud Rate:** 19200
- **Power Supply:** 24V/2.7A DC (US/EU standards, CE/FCC/UL certified)
- **ESD Protection:** Human Body Model:
 - ±12kV (Air Discharge)
 - ±8kV (Contact Discharge)
- **Dimensions (WxHxD):** 9.1 x 1 x 6.2 in (231.5x25x158mm) [Case Only] / 9.1 x 1 x 6.3 in (231.5x25x161mm) [All Inclusive]
- **Weight:** 2.1 lb / 968g
- **Chassis Material:** Metal (Steel)
- **Chassis Color:** Black
- **Operating Temperature:** 0°C - 40°C/32°F - 104°F
- **Storage Temperature:** -20°C - 60°C/-4°F - 140°F
- **Relative Humidity:** 20 - 90% RH (Non-condensing)
- **Power Consumption:** 15.3W