

A-NeuVideo ANI-44HPSC 4x4 4K60 HDR HDMI Matrix Routing Switcher with 1080 Down Scaling/Analog Audio Output

- **HDMI Bandwidth:** 18Gbps
- **Input Ports:** (4) HDMI (Type-A)
- **Output Ports:**
 - (4) HDMI (Type-A)
 - (4) Analog Stereo (3.5mm)
- **Control Ports:**
 - RS-232 (DE-9)
 - Ethernet (RJ-45)
 - IR Extender (3.5mm)
- **Service Port:** USB 2.0 (Type A)
- **IR Frequency:** 38kHz
- **Baud Rate:** 19200
- **Power Supply:** 24V/2.7A DC (US/EU standards, CE/FCC/UL certified)
- **ESD Protection: Human Body Model:**
 - ±8kV (air-gap discharge)
 - ±4kV (contact discharge)
- **Dimensions (WxDxH):** 17.2 x 1.9 x 10.6 in (438x49x269mm) [Case Only] / 19 x 1.9 x 10.8 in (482x49x274mm) [All Inclusive]
- **Weight:** 6.6lb / 2.99kg
- **Chassis Material:** Metal (Steel)
- **Color:** Black
- **Operating Temperature:** 0°C - 40°C/32°F - 104°F
- **Storage Temperature:** -20°C - 60°C/-4°F - 140°F
- **Relative Humidity:** 20 - 90% RH (Non-condensing)
- **Power Consumption:** 34W