



## 691

4K60 4:2:0 HDMI MM/SM Fiber Optic Transmitter with USB, Ethernet, RS232, IR & Stereo Audio over UltraReach HDBaseT 2.0

| HDMI | Fiber Optic | Ethernet - RJ-45  
| HDBaseT



691 is a highperformance HDBaseT 2.0 fiber transmitter for ultrareach extension of 4K60Hz (4:2:0) HDMI, USB, Ethernet, RS232, IR and stereo audio signals over either multimode or singlemode fiber optic. 691 converts all input signals into the transmitted HDBaseT 2.0 signal over fiber optics. The extended line receiver, such as Kramer 692, converts the HDBaseT 2.0 signal back to 4K60Hz (4:2:0) HDMI, USB 2.0, Ethernet, RS232, IR and stereo audio output signals. 691 extends video signals to up to 33km (20.5 miles) over singlemode fiber at up to 4K@60Hz (4:2:0) resolution

## FEATURES

**High Performance Standard Fiber Extender** - HDBaseT 2.0 fiber transmitter for providing ultrareach signals over either multimode or singlemode optical fiber infrastructures, using Kramer pluggable OSP SFP+ units. 691 is a standard fiber extender that can be connected to any marketavailable HDBaseTcompliant extension product.

Note: To ensure Kramer support and warranty of the 691 product, use only Kramer's certified hipformance OSP SFP+ pluggable optical units. For optimum extension reach and performance, use Kramer's OSP SFP+ units and recommended Kramer cables. NonKramer cables may not reach these ranges

**HDMI Signal Extension** - HDMI 2.0 and HDCP 1.4 compliant. Supports deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTSHD, 2K, 4K, and 3D. EDID and CEC signals are passed through from the source to the display

**IEDIDPro™ Kramer Intelligent EDID Processing™** - Intelligent EDID handling, processing and passthrough algorithm that ensures Plug and Play operation for HDMI source and display systems

**USB Extension** - USB 2.0 interface data flows in both directions, allowing extension of HID (Human Interface Devices) peripheral devices, such as a mouse or a keyboard. Highbandwidth USB peripheral devices, such as USB isochronous streaming cameras and audio devices, transfer data continuously and periodically. Delivery of their transferred data is not guaranteed by the USB standard and is subject to both USB and HDBaseT line bandwidth management limitations. When such devices are connected, check their functionality to ensure bandwidth limitations are not exceeded

**Ethernet Extension** - Ethernet interface data flows in both directions allowing extension of up to 100Mbps Ethernet connectivity for LAN communication and device control

**Bidirectional RS232 Extension** - Serial interface data flows in both directions allowing data transmission and device control

**Bidirectional Infrared Extension** - IR interface data flows in both directions allowing remote control of peripheral devices located at either end of the extended line

**Audio Embedding (Adding)** - A selectable analog unbalanced stereo audio input is converted into a digital signal and added (embedded) to the transmitted HDMI signal, replacing the embedded HDMI audio input signal. This enables embedding a selectable audio source over HDMI. For example, a presenter can display a video clip and temporarily override the audio of the source media with another audio source, such as from a microphone

**Cost-Effective Maintenance** - Status LED indicators for the HDMI input and HDBT output link facilitate easy local maintenance and troubleshooting. Remote device management via builtin web UI, RS232 connection, and Kramer Network. Local and remote firmware upgrade via miniUSB, RS232 or Ethernet connection and the KUpload tool ensure lasting fieldproven deployment

**Easy Installation** - Half 19" 1U rack mountable fanless enclosure enables sidebyside mounting of 2 units in a 1U rack space



# KRAMER

## TECHNICAL SPECIFICATIONS

---

INPUTS:	1 HDMI on HDMI connector, 1 stereo analog unbalanced audio on a 3.5mm mini jack
OUTPUTS:	1 fiber optic on a 10Gbps SFP+ LC connector complying with IEEE 802.3ae
PORTS:	1 IR on a 3.5mm mini jack for IR link extension, 1 USB on a female USBB connector for USB link extension, 1 RS232 on a 3pin terminal block for serial link extension, 1 RS232 on a 3pin terminal block for transmitter control, 1 100BaseT Ethernet on an RJ45 female connector for device control and LAN extension
EXTENSION LINE:	HDBaseT 2.0 compliant; Multimode (MM) or singlemode (SM) optical fiber, 2 simplex fiber strands
MULTIMODE LINE:	G.651.1 compliant OFNR fiber, 850 nm nominal peak wavelength, 10.2Gbps max data rate, 2.5dBm typical optical transmission power, 8.6dB typical optical maximum loss budget, Up to 3km (1.8 miles) reach over OM3 MM fiber
SINGLEMODE LINE:	G.652D compliant OFNR fiber, 1310 nm nominal peak wavelength, 10.2Gbps max data rate, 2.5dBm typical optical transmission power, 11.9dB typical optical maximum loss budget, Up to 33Km (20.5 miles) reach over OS1 SM fiber
VIDEO:	Up to 10.2Gbps bandwidth (3.4Gbps per graphic channel), up to 4K UHD @60Hz (4:2:0) 24bpp resolution, HDMI 2.0 and HDCP 1.4 signal compliance
AUDIO:	Up to 1 Vrms level, 0.03% THD + noise @1kHz at nominal level
EXTENDED USB:	1.1 and 2.0 host compliance, Up to 127Mbps (out of max 480 USB) extended line rate bandwidth, Up to 7 devices, Up to 2 hubs, Up to 8 ports per hub
EXTENDED ETHERNET:	Up to 100Mbps Ethernet transmission bandwidth
EXTENDED RS-232:	300 to 115200 baud rate
PRODUCT DIMENSION:	21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72" ) W, D, H
PRODUCT WEIGHT:	1.0kg (2.1lbs) approx
SHIPPING DIMENSION:	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83" ) W, D, H
SHIPPING WEIGHT:	1.5kg (3.2lbs) approx
CONTROL RS-232:	115200 baud rate
SUPPORTED PC WEB BROWSERS:	Windows 7 and higher: Internet Explorer (32/64 bit) version 10, Firefox version 30, Chrome version 35 MAC:Chrome version 35, Firefox version 30, Safari version 7, Note: Minimum browser window size 1024 x 768

POWER SOURCE: 12V DC, 1.36A

POWER CONSUMPTION: 12V DC, 600mA

ENCLOSURE: Half 19" 1U rack unit size, aluminium type

COOLING: Convection ventilation

OPERATING TEMPERATURE: 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE: 40° to +70°C (40° to 158°F)

HUMIDITY: 10% to 90%, RHL noncondensing

VIBRATION: ISTA 1A in carton (International Safe Transit Association)

SAFETY REGULATORY COMPLIANCE: CE, UL

ENVIRONMENTAL REGULATORY COMPLIANCE: Complies with appropriate requirements of RoHs and WEEE

INCLUDED ACCESSORIES: Power supply (12V, 1.36A)



# KRAMER

## CONFIGURATIONS

691	691, PSU + Power cord, Screwdriver
OSP-MM1	Optical MM 850nm 10G SFP+ Transceiver
OSP-SM10	Optical SM 1310nm 10G SFP+ Transceiver
691/2-MM1 Kit	691 + 692 + 2 x OSP-MM1 Kit
691/2-SM10 Kit	691 + 692 + 2 x OSP-SM10 Kit

