

Kramer 860 4K/60 4x4x4 HDCP 2.2 HDMI 2.0 18G Signal Generator/Analyzer

INPUTS

- 1 HDMI, 1 unbalanced stereo audio (2Vrms max. 20kΩ) on a 3.5mm jack, 1 RS-232 on a 9-pin D-sub connector, 1 Ethernet on an RJ-45 connector, 1 USB connector

OUTPUTS

- 1 HDMI, 1 VGA on a 15-pin HD connector, 1 unbalanced stereo audio (2Vrms max. 560Ω) on a 3.5mm jack

COMPLIANCE WITH HDMI STANDARD

- Up to HDMI 2.0 and HDCP 2.2

CONTROLS

- Panel buttons with OLED display, OSD, RS-232, IR, and Ethernet

MAXIMUM DATA RATE

- 18Gbps (6Gbps per graphic channel)

ESD PROTECTION

- Human body model: ±8 kV (air-gap discharge), ±4 kV (contact discharge)

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -20° to +60°C (-4° to 140°F)

HUMIDITY

- 20% to 90%, RHL non-condensing

POWER CONSUMPTION

- 5V DC, 1.6A

POWER SUPPLY

- 5.2V/4A

CHASSIS MATERIAL

- Metal

SAFETY REGULATORY COMPLIANCE

- CE

INCLUDED ACCESSORIES

- Remote control (LR-40), power supply

PRODUCT DIMENSION

- 16.50cm x 13.20cm x 3.00cm (6.50" x 5.20" x 1.18") W, D, H

PRODUCT WEIGHT

- 0.8kg (1.7lbs) approx

SHIPPING DIMENSION

- 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H

SHIPPING WEIGHT

- 1.2kg (2.7lbs) approx