

Roland S-0808 8x8 Input/Output Unit

Feature	Function	Benefit
Battery-powered	Power can be supplied by a standard IDX or Anton Bauer battery.	Provides convenient power supply method for location and remote applications where AC is not available or practical.
REAC Embedded Power	Power can be supplied via the S-4000D or S-4000M through Cat5e cable or a 3rd party POE unit.	Allows for convenient powering when using as part of REAC merge and personal mixing applications.
Power over Ethernet	Power can be supplied using a compatible 3rd party high-powered Power over Ethernet (PoE) injector.	Supply power to an S-0808 in any location when an S-4000D or S-4000M is not being used.
Included Battery Mount Adapter Plate	Mount V-Mount (IDX) or Gold Mount (Anton Bauer) battery plate on the side.	Mounting battery plate is convenient and ready to go. All screws included.
No heat fans	100% silent operation	Allows close placement of S-0808 to microphone sources
Hi-Z Inputs	Two 1/4" inputs equipped with Hi-Z capability for direct connection of instruments.	No need for external direct boxes when using guitars.
TRS Inputs	Connect up to four V* TRS line level sources	Directly connect keyboards and other instruments without the need for adapters or direct boxes
Remote Controlled Mic Preamps	Control phantom power, 20dB pad and gain using the S-4000R or PC remote control software (S-4000RCS).	Control gain structure from either end of the snake including saving frequently used configurations.