

Specifications

Video

Standards	DVI (single link) HDMI 1.4 video specifications including 12 bit color depth, 3D video HDCP 1.4
Connectors	ULTRA-V-4S (1) HDMI Input (1) HDMI Output (4) RJ45 Outputs (1) Mini-USB Service Port (1) 2.0MM Locking DC Power Input
Refresh Rates	60 Hz for resolutions upto and including HD (1920x1080) and WUXGA (1920x1200) 30 Hz for resolutions above and including QHD (2560x1440)
Resolutions	DVI signal VGA (640x480) thru WUXGA (1920x1200) HDTV signal 480p through 4K60 4:2:0 (Interlaced resolutions are not supported)

General

Power Supply	100 VAC to 240 VAC, 47-63 Hz, External; 5 VDC
Temp/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, non-condensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, non-condensing
Power	5 VDC, 4.0 A Power Supply
Cooling	Convection
Enclosure type	Metal (Steel)
Dimensions	ULTRA-V-4S:
Product weight	Model Only ULTRA-V-4S: 1.83 lbs (0.83 kg)
	Shipping ULTRA-V-4S: 3.5 lbs (1.6 kg)
Safety	CE
EMI/EMC	CE, FCC Class A
MTBF	90,000 hours (estimate)
Warranty	3 years parts and labor

Specifications are subject to change without notice