

## BZBGEAR BG-AVTPG-MINI 1080P FHD/4K UHD HDMI 2.0 18Gbps Portable Signal Test Generator and Analyzer

Role of usage	HDMI 2.0a Installation Gear	
Video bandwidth	Single link 600MHz [18Gbps]	
HDMI compliance	HDMI 2.0 and below	
HDCP compliance	HDCP 2.2 and below	
Video Support	up to 4K @ 60 4:4:4 8bit, 4K2K @ 60 4:2:0 16bit (HDR)	
ESD protection	Human body model — ±15kV [air-gap discharge] & ±8kV [contact discharge]	
Video Format Support	HDMI	
Input	1x HDMI	
Output	1x HDMI	
Control	Push Button	
HDMI connector	Type A [19-pin female]	
USB Support	Firmware update / Recharge	
USB connector	Micro-USB (Type B)	
<b>Mechanical</b>		
Enclosure	Metal case	
Dimensions (L x W x H)	Model	5.1" x 3.5" x 0.6" [130 x 89 x 14mm]
	Package	7.8" x 5.4" x 2.9" [198 x 137 x 74mm]
Weight	Model	7.8oz [220g]
	Package	11.3oz [320g]
Power supply	Micro-USB / Battery	
Power Consumption	5W [MAX]	
Operation temperature	32~104°F / 0~40°C	
Storage temperature	-4~140°F / -20~60°C	
Relative humidity	20~90% RH [no condensation]	