

Kramer C-5BM/5BM-50 50ft 5 BNC RGBHV Mini Coax Cable

| | |
|---------------------------|---|
| Coax Center Conductor: | 28 AWG 7/36 tinned copper. |
| Dielectric: | Foam polyethylene. |
| Shield: | 90% braid 38 AWG tinned copper. |
| Coax Jacket Colors: | Red, green, blue, yellow, black. |
| Outer Jacket: | PVC. |
| Outer Jacket Color: | Dark gray with white lettering. |
| DIAMETERS | |
| Center Conductor: | 0.38mm (0.015in). |
| Individual Coax: | 2.75mm (0.108in). |
| Outside Diameter: | 9.2mm (0.362in). |
| ELECTRICAL | |
| Impedance: | 75ohm. |
| DC Resistance: | 237ohm/km (72.2ohm/1000ft). |
| Capacitance: | 60pF/m (18.3pF/ft). |
| Velocity of Propagation: | 78%. |
| Temperature: | -20° to +75°C (-4° to +167°F). |
| Attenuation (dB/100 ft.): | -0.6dB @1MHz -1.4dB @5MHz -2.1dB @10MHz -4.7dB @50MHz -6.8dB @100MHz -9.2dB @180MHz -14.2dB @400MHz -20.1dB @750MHz -23.8dB @1000MHz. |
| REGULATORY | |
| UL: | CL2. |
| CSA: | C(UL) CL2. |
| | |
| Dielectric: | 1.6mm (0.063in). |