

Roland V-1SDI-W 4-Channel SDI/HDMI 3G-SDI Video Switcher Streaming Bundle

3G-SDI Video Switcher - 4 Channel SDI/HDMI	
VIDEO	
Video Processing	4:2:2 (Y/Pb/Pr), 8-bit
Input Connectors	SDI INPUT 1--3: BNC x 3 * Conforms to SMPTE 424M (SMPTE 425M-AB), 292M HDMI INPUT 3--4: Type A (19 pins) x 2 * HDCP Supported * INPUT 3: SDI or HDMI selected.
Output Connectors	SDI OUT PGM: BNC x 1 SDI OUT PVW: BNC x 1 * Conforms to SMPTE 424M (SMPTE 425M-AB), 292M HDMI OUT MULTI-VIEW: Type A (19 pins) x 1 * HDCP Supported
Input Formats	SDI INPUT 1-3 Conforms to SMPTE 296M, SMPTE 274M HDMI INPUT 3 720/59.94p, 720/50p SMPTE 296M(FORMAT switch = 720p) 1080/59.94i, 1080/50i, 1080/59.94p, 1080/50p SMPTE 274M(FORMAT switch = 1080i or 1080p) * The input interlaced video signal is converted to progressive video signal by internal processing. * The video signal frame rate can be selected at the SETUP menu (59.94 or 50). HDMI INPUT 4 480/59.94i, 576/50i, 480/59.94p, 576/50p, 720/59.94p, 720/50p, 1080/59.94i, 1080/50i, 1080/59.94p, 1080/50p VGA (640 x 480/60 Hz), SVGA (800 x 600/60 Hz), XGA (1024 x 768/60 Hz) WXGA (1280 x 768/60 Hz), SXGA (1280 x 1024/60 Hz) FWXGA (1366 x 768/60 Hz), SXGA+ (1400 x 1050/60 Hz) UXGA (1600 x 1200/60 Hz), WUXGA (1920 x 1200/60 Hz) * The refresh rate is the maximum value of each resolution. * Conforms to VESA DMT Version 1.0 Revision 11. * 1920 x 1200/60 Hz: Reduced blanking. * The input interlaced video signal is converted to progressive video signal by internal processing. * The video signal frame rate can be selected at the SETUP menu (59.94 or 50).
Output Formats	SDI OUT(PGM/PVW) Conforms to SMPTE 296M, 274M HDMI OUT MULTI-VIEW 720/59.94p, 720/50p SMPTE 296M(FORMAT switch = 720p) 1080/59.94i, 1080/50i SMPTE 274M(FORMAT switch = 1080i) 1080/59.94p, 1080/50p SMPTE 274M(FORMAT switch = 1080p) * The video signal frame rate can be selected at the SETUP menu (59.94 or 50).
Video Effects	Transition: CUT, MIX (DISSOLVE/FAM/NAM/MOSAIC), WIPE (30 types) Composition: PinP, SPLIT, QUAD, DSK (Luminance Key, Chroma Key)
AUDIO	
Audio Processing	Sampling rate: 24 bits/48 kHz
Audio Formats	SDI: Linear PCM, 24 bits/48 kHz, 2ch Conforms to SMPTE 299M HDMI: Linear PCM, 24 bits/48 kHz, 2ch
Input Connectors	Digital: SDI INPUT 1--3 (BNC) x 3 SMPTE 299M HDMI INPUT 3--4 (HDMI Type A 19 pins) x 2 Analog: AUDIO IN (RCA phono type) MIC (Stereo mini type, plug-in power supported)

Output Connectors	Digital: SDI OUT PGM: BNC x 1 SMPTE 299M SDI OUT PVW: BNC x 1 SMPTE 299M HDMI OUT MULTI-VIEW: Type A (19 pins) x 1 Analog: AUDIO OUT (RCA phono type) PHONES (Stereo mini type)
Input Level	AUDIO IN: -10 dBu (Maximum: +8 dBu) MIC: -41-- -13 dBu (Maximum: -1 dBu)
Input Impedance	AUDIO IN: 15 k ohms MIC: 10 k ohms
Output Level	AUDIO OUT: -10 dBu (Maximum: +8 dBu) PHONES: 92 mW + 92 mW (32 ohms)
Output Impedance	AUDIO OUT: 1 k ohm PHONES: 10 ohms
OTHERS	
Other Connectors	USB: B Type (for remote control from PC) RS-232: DB-9 type
Other Functions	MEMORY (8 types) FREEZE (input video captured) OUTPUT FADE (Audio, Video: WHITE or BLACK)
Power Supply	AC Adaptor
Current Draw	2.1 A
Power Consumption	25 W
Operation Temperature	+0 to +40 degrees Celsius +32 to +104 degrees Fahrenheit
Dimensions	313 (W) x 108 (D) x 59 (H) mm 12-1/3 (W) x 4-1/4 (D) x 2-1/3 (H) inches
Weight (excluding AC adaptor)	1.2 kg 2 lbs 10-2/5 oz
Magewell USB Capture SDI Gen 2	
Supported OS	Windows 10, 8.1, 8, 7, 2012 (x86/x64), 2008 R2, 2008 Linux (Ubuntu 12.04-16.10, CentOS 7) OS X 10.9-10.11 macOS 10.12 Chrome OS
Supported APIs	Windows: DirectShow Wave API/DirectSound/WASAPI Linux: V4L2 ALSA OS X/macOS: QuickTime AV Foundation
Input	1 x Mini Coax (MCX) port (supporting 3G/HD/SD-SDI signals via an included MCX to SDI cable)
Output	USB 3.0 (compatible with USB 3.1 Gen 1, backwards-compatible with USB 2.0)
USB Standard	Meets the standards of UVC (USB video class) and UAC■USB audio class■
Supported Resolutions	Input/Output: Up to 2048 x 1080 (2K) at 60 Hz
Power Consumption	5 V max current: 0.5 A Max power consumption: 2.5 W
Operating Temperature	32 to 122°F (0 to 50°C)
Storage Temperature	4- to 158°F (-20 to 70°C)
Relative Humidity	5 to 90% non-condensing
Dimensions	3.6 x 1.6 x 0.5" (9.2 x 4 x 1.2 cm)